

# RESPIRATORY GEAR P2 DISPOSABLE RESPIRATOR

PRODUCT DATA SHEET: PC305



PRODUCT CODE:  
PC305



## FEATURES AND BENEFITS

- Suitable for use with dust, smoke, mist & fume
- Lightweight moulded design with foam nose seal for comfort and superior fit.
- Easily worn with glasses & goggles.
- P2 Certified to AS/NZS 1716:2012 Respiratory Protective Devices
- Dual latex free elastic straps for ease of donning & doffing.
- Resealable bag for hygienic storage

## AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
PC305	BOX	1	20

## PRODUCT DETAILS

**Straps:** Latex-Free Rubber  
**Filter Media:** Polypropylene Melt-blown  
**Weight:** 12g +/- 5g each  
**Nose Flange:** PU Foam

## CARE INSTRUCTIONS

Shelf life of the unopened product is three (3) years from date of manufacture when stored within the temperature range of -5°C to +50°C and less than 80% relative humidity.

End of shelf life date is marked on the product packaging. Before initial use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.



HYGIENIC



PARTICULATE PROTECTION



RETAINS SHAPE



VALUE

## WARNINGS AND USE LIMITATIONS

- Facial hair has the potential to compromise the required protective seal of the respirator
- Ensure adequate oxygen levels are present
- Ensure the contamination is known and the respirator is suitable for the application
- Replace when taste, smell or the breathing resistance is high
- Store in a clean, resealable storage device

## STANDARDS

**CERTIFIED TO:**  
**AS/NZS 1716:2012** Respiratory Protective Devices  
 Certified by Benchmark  
**Identification number:** BMP547903



AS/NZS2161.3  
 ID No: **BMP547903**

To be used in conjunction with:  
**AS/NZS 1715:2009** - Selection, Use and Maintenance of Respiratory Protective Equipment

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

**PARAMOUNT SAFETY PRODUCTS AUSTRALIA**  
 12 FELLOWSHIP ROAD,  
 GNANGARA, WA 6077  
 TECH SUPPORT: 1300 275 820  
 CUSTOMER SERVICE: 1300 770 723  
 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

**PARAMOUNT SAFETY PRODUCTS NEW ZEALAND**  
 7 SIR WOOLF FISHER DRIVE, Highbrook,  
 EAST TAMAKI, AUCKLAND 2013  
 TECH SUPPORT: 0800 888 778  
 CUSTOMER SERVICE: 0800 888 778  
 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM  
 PARAMOUNTSAFETY.COM

**PRO**  
 PRO CHOICE SAFETY GEAR  
 FROM  
**PARAMOUNT**  
 SAFETY PRODUCTS